


# Folder-Gluer Belts


Consistent and precise folding with no marking



Habasit's folder-gluer belts provide excellent folding and maximize machine performance. The comprehensive range includes options of polyamide or polyester composite for the traction layer and NBR rubber covers. From box folding to tube winding, the belts are ideal for a wide range of applications.

- Longer service life due to exceptional abrasion resistance
- Consistent, precise folding without marking your goods
- FDA and EU-compliant belts are available

**Visit our website for the latest innovations:**  
<https://rebrand.ly/FolderGluer>



Our belts and tools facilitate Thermofix (top) and Flexproof (bottom) joints.

# Folder-Gluer Belts

Belt type	Belt speed m/min	Thickness mm (in.)	Pulley diameter mm (in.)	K1% N/mm (lbf/in.)	Conveying side (Color)	Pulley side (Color)	Traction layer
<b>Flexproof fusion joint (finger joint)</b>							
FT-18/30E°	700	3 (0.12)	30 (1.18)	18 (102.8)	Thermoplastic Alloy (Light gray)	Thermoplastic Alloy (Light gray)	Polyester
FT-18/40E°	700	4 (0.16)	30 (1.18)	18 (102.8)	Thermoplastic Alloy (Light gray)	Thermoplastic Alloy (Light gray)	Polyester
CM-4/30F	300	3 (0.12)	40 (1.57)	4.0 (23)	NBR (Light green)	NBR (Yellow)	Polyamide
CM-4/40F	300	4 (0.16)	50 (1.97)	4.0 (23)	NBR (Light green)	NBR (Yellow)	Polyamide
CM-4/50F	300	5 (0.20)	60 (2.36)	4.0 (23)	NBR (Light green)	NBR (Yellow)	Polyamide
<b>Thermofix bonded joint (skived joint with adhesive)</b>							
FR-10/30	600	3 (0.12)	30 (1.18)	5.0 (29)	NBR (Light green)	NBR (Yellow)	Polyamide
FR-10/40	600	4 (0.16)	40 (1.57)	5.0 (29)	NBR (Light green)	NBR (Yellow)	Polyamide
FR-18/60	600	6 (0.24)	60 (2.36)	7.5 (43)	NBR (Light green)	NBR (Yellow)	Polyamide

°Compliant with FDA and EU regulations.

Product sub-group	Appearance	Features	Max. width mm (in.)	Max. thickness mm (in.)	Dimensions (mm)			Weight kg (lb.)	Power
					L	W	H		
<b>AF-100/US</b> Die-cutting tool		Precisely cuts belt ends for Flexproof finger joints.	100 (3.94)	6 (0.24)	615	650	270	14 (29.8)	N/A
<b>AF-102</b> Die-cutting tool		Precision device for cutting machine tapes.	100 (3.94)	2 (0.08)	200	52	85	1.6 (3.5)	N/A
<b>AT-60</b> Skiving tool		Versatile skiving device for belt preparation.	60 (2.36)	2 (0.08)	220	190	85	1.5 (3.3)	N/A
<b>PF-62</b> Hot press		Efficient in tight and low-visibility areas.	60 (2.36)	5 (0.18)	320	176	116	2 (4)	120V*
<b>PF-100S</b> Hot press		Adjustable to different belt thicknesses.	100 (4)	3 (0.10)	285	102	102	2 (4.4)	120V*
<b>PF-101</b> Hot press		Can join both Flexproof and Thermofix belts.	100 (4)	6 (0.24)	260	190	145	4 (8.2)	120V*

\*230V version also available. For the full product data sheets, please visit [portal.habasit.com](http://portal.habasit.com)

Information provided herein does not constitute legal representations or warranties and may change without notice. Please refer to the specifications/disclaimers provided in the respective product data sheets.

For further information choose country selection Habasit Worldwide on:  
[www.habasitamerica.com](http://www.habasitamerica.com)

Habasit America  
805 Satellite Blvd  
Suwanee, GA 30024  
Phone: 800.458.6431  
Fax: 678.288.3654  
E-mail: [habasit.america@habasit.com](mailto:habasit.america@habasit.com)

Copyright Habasit AG  
Subject to alterations

4715FLY.FGB-en1124HUS